

Suction hoses for fire fighting use



2900

The suction hoses DIN EN ISO 14 557, Type A, are smooth inside, black ribbed outside, SBR-Quality (Styrol-Butadien-Caoutchouc) without external spiral. Couplings attached in both spiral free ends. Ozone resistance acc. to ISO 7326 : 1991. Test Certificate number ZPC 5002 for A-110 available.

Storz System Connection

Inside dia. (mm)	Nominal size Storz	Length (mm)	Weight (kg)	Ident.No.	Remarks
52	2 x C	1580	3,050	60128400	
52	2 x C	1600	4,850	60467300	¹⁾
52	2 x C	3080	5,650	60256400	
65	2 x 65	2000	6,000	60577400	
75	2 x B	1585	5,300	60128500	
75	2 x B	1985	6,800	60252800	
75	2 x B	2485	7,000	60215200	
110	2 x A	1600	11,000	60128600	
110	2 x A	1600	11,200	60128699	with folding handles
110	2 x A	1600	11,200	60465100	predrilled for folding handles Scharfenberg
110	2 x A	1600	12,000	60418500	with folding handles Scharfenberg
110	2 x A	2000	13,000	60216300	
110	2 x A	2150	13,500	60473800	
110	2 x A	2500	13,600	60128700	
110	2 x A	2500	14,700	60128799	with folding handles
110	2 x A	3000	17,000	60495200	
110	2 x A	4000	20,000	60486600	
125	2 x 125	1600	11,500	60486100	
125	2 x 125	2000	15,000	60454000	
125	2 x 125	2000	15,500	60523800	with folding handles



Inside dia. (mm)	Nominal size Storz	Length (mm)	Weight (kg)	Ident.No.	Remarks
125	2 x 125	2500	19,800	60582000	

Other dimensions and lengths as well as other connections on request.