

## Blank caps


- Aluminium alloys (A)
- Copper alloys (C)
- High grade steel (St)

### Blank caps with chain



1300

Used to shut Storz connections fitted on pipes, fittings and other equipment. A chain is standard, if not marked otherwise.



1300



1302



1303 A



1303 B

Nominal size	Lug spacing b (mm)	Face-to-face length L (mm)	Weight (kg)	Ident.No.	Remarks	Alloy
25=D-DS	31	28	0,090	40241433	DIN 14 310	A
25=D-DS	31	28	0,090	60463033	seal white	A
25=D-DS	31	28	0,090	40241432	cast PN 10	A
25=D-DS	31	28	0,200	40324846		A
25=D-DS	31	28	0,255	40241493		A
32-DS	44	32	0,115	40241533		A
32-DS	44	32	0,325	40241593		A
38-DS	51	35	0,195	40247333		A
38-DS	51	35	0,540	40247393		A
45-DS	59	39	0,215	40247433		A

Nominal size	Lug spacing b (mm)	Face-to-face length L (mm)	Weight (kg)	Ident.No.	Remarks	Alloy
52=C-DS	66	43	0,230	60309159	complete Polyamid PN 10	A
52=C-DS	66	43	0,320	60106033	without chain	A
52=C-DS	66	43	0,340	60309132	cast PN 10	A
52=C-DS	66	43	0,355	40247633	DIN 14311	A
52=C-DS	66	43	0,355	60469333	seal silicone	A
52=C-DS	66	43	0,390	60661533	with automatic air bleeder (1303)	A
52=C-DS	66	43	0,400	60152633	with drain valve (1302)	A
52=C-DS	66	43	0,410	60462033	with automatic air bleeder (1303 A)	A
52=C-DS	66	43	0,760	40029846		A
52=C-DS	66	43	0,775	60139293	without chain	A
52=C	66	43	0,800	40250893	DIN 86206 Form "K"	A
52=C	66	43	0,920	40229393	DIN 86206 Form "L"	A
52	75	32	0,150	50314733	autom. air bleeder (1303 A) <sup>2)</sup>	A
65	81	34	0,400	60023133	without chain	A
65	81	34	0,410	40247733	NEN 3374	A
65	81	34	0,410	40247732	cast PN 10	A
65	81	34	1,230	40247793		A
65-DS	81	35	1,100	60459446		A
75=B-DS	89	45	0,500	60028233	without chain	A
75=B-DS	89	45	0,515	60289732	cast PN 10	A
75=B-DS	89	45	0,520	60469433	seal silicone	A
75=B-DS	89	45	0,525	40247833	DIN 14312	A
75=B-DS	89	45	0,570	60659933	with non-return valve <sup>3)</sup>	A
75=B-DS	89	45	0,600	60462133	with automatic air bleeder (1303 A)	A
75=B-DS	89	45	0,600	60150033	with drain valve (1302)	A
75=B-DS	89	45	1,200	40251093	DIN 86207 Form "K" <sup>1)</sup>	A
75=B-DS	89	45	1,250	40030346		A
75=B-DS	89	45	1,460	40229593	DIN 86207 Form "L"	A
90-DS	105	45	0,750	40248633		A
100	115	45	2,540	40248193	cast PN 10	A
100-DS	115	45	2,600	60418846		A
100	115	47	0,950	40248033		A
110=A	133	34	0,285	20207259	one part, Polyamid PN 2,5	A
110=A-DS	133	48	1,290	60469533	seal silicone	A
110=A-DS	133	48	1,290	60029233	without chain	A
110=A-DS	133	48	1,290	40248733	DIN 14313	A
110=A-DS	133	48	1,300	60289832	cast PN 10	A
110=A-DS	133	48	1,300	60224733	with drain valve (1302)	A
110=A-DS	133	48	1,860	60106933	with folding handles	A
110=A-DS	133	48	2,900	40320346		A
110=A-DS	133	48	3,600	40249093	cast PN 10	A

Nominal size	Lug spacing b (mm)	Face-to-face length L (mm)	Weight (kg)	Ident-No.	Remarks	Alloy
125-DS	148	52	1,610	40249533		A
125-DS	148	52	4,800	40249546		A
125-DS	148	52	4,900	40249293	cast PN 10	A
135-DS	159	55	1,900	40249633	cast PN 10	A
150-DS	160	56	2,350	40249833	with 3 lugs	A
150-DS	160	56	7,600	40249895	with 3 lugs, cast PN 10	A
150-DS	160	56	7,600	60464746	with 3 lugs	A
165-DS	188	64	2,800	40250033	cast PN 10	A
205-DS	220	75	4,220	40250433	cast PN 10	A
205-DS	220	75	4,220	60588933	<b>Jumbo</b> Storz 8", 3 lugs	A
250-DS	278	82	7,900	60669533	<b>Jumbo</b> Storz 10", with 3 lugs	A
305	316	88	14,800	60669633	<b>Jumbo</b> Storz 12", with 3 lugs	A