

Extinguishing Bucket

Very reliable as piston pump works in both directions. Suitable for extinguishing starting fires of class A. The bucket will be emptied in less than one minute.

Available styles:

A-10/3900 Jet nozzle DK DIN 14 405 and adapters DIN 14 306 resp. coupl. DIN 14 301, hose 5 m, D 25 DIN 14811. Synthetic, internally rubber coated.

B-10/3901 Screws copper alloy, hose 1 m, 1/2" i. d. PVC, nozzle polyamide.

Extinguishing Bucket



3900

Very reliable as piston pump works in both directions. Suitable for extinguishing starting fires of class A. The bucket will be emptied in less than one minute.

Available styles:

A-10/3900 Jet nozzle DK DIN 14 405 and adapters DIN 14 306 resp. coupl. DIN 14 301, hose 5 m, D 25 DIN 14811. Synthetic, internally rubber coated.

B-10/3901 Screws copper alloy, hose 1 m, 1/2" i. d. PVC, nozzle polyamide.



3901

Style / Nominal size	Outside Ø base (mm)	Volume (Ltr.)	Height (mm)	Weight (kg)	Style	Ident-No.	Remarks
A 10	200	10	663	7,600	3900	60210444	DIN 14 405
A 10	200	10	663	6,500	3900	60483144	without hose
B 10	200	10	663	6,400	3901	60483344	DIN 14 405

As per: 09.05.2009