

GALAXY 3.2

* 4500 lm

RDLO013-1

APPLICATIONS: MEDICAL, INDUSTRIAL, MILITARY, RESCUE, CAMPING, CONSTRUCTION

POWER SUPPLY	230V AC / 50-60 Hz
POWER	30W
LIGHT OUTPUT	4500 lm
OPERATING TEMPERATURE	-35° C - +50° C
LIFETIME	80 000 h
HOUSING	aluminum, polycarbonate
DIMENSIONS	308 x 104 x 98,15 mm
WEIGHT	2,23 kg
THE SET INCLUDES	RDLO013-1: 5-meter power/connecting cord and Schuko plug and Schuko socket on the output, hanging metal string with lamp mounts -> FIRST AND/OR NEXT LAMP IN SERIES



- IP66 RATING
- IK10 RATING
- ON/OFF SWITCH
- SCHUKO



Galaxy 3.2 is a lamp designed for military shelters, evacuation tents, and field hospitals. It emits 4500 lm of white light, perfectly illuminating interiors. The Galaxy system allows for connecting up to 10 lamps, each with an individual switch and a 5 m power cord with Schuko connectors (IP68). The aluminum and polycarbonate housing guarantees the mechanical resistance of IK10, and the IP66 rating protects against dust and strong water jets from any direction. The lamp operates in temperatures ranging from -35°C to +50°C. A 230V AC mains power consumes 30W of power and lasts 80,000 hours.

PRODUCT MEETS THE FOLLOWING STANDARDS:

MACTRONIC[®]
VALUE
HIGHLIGHTS

5-YEAR
WARRANTY

PATENTED
DESIGN

ECO FRIENDLY
PACKAGING

