



USER INFORMATION
EN388:2018
EN381-7

0524 : 7330 G11 - TAKE OUT UKCA MARK,
APPROVED BODY ADDRESS AND THE 0321 IN THE
TABLE. CHANGE EN 388 LEVELS TO 2122X

EXCEL LOCATION

http://192.168.8.156/Current/Product Range/USER SHEETS/2016-EXCEL MASTER FILES/GLOVES/EXCEL-GLOVE MASTER/GLOVE MASTER_1217.xlsx

MASTER FILE LOCATION: GRAPHICS - Location: CURRENT:Product Range:04.GLOVES ARTWORK MASTER_04. USERSHEETS:01. STANDARD BASED:2023-USERSHEETS:G11-SINGLE-0524

PORTWEST®

CE 2777

EN 388:2016+A1:2018
EN ISO 11393-4:2019
EN ISO 21420:2020

G11 

MANUFACTURERS ADDRESS: PORTWEST, IDA BUSINESS PARK, WESTPORT, CO MAYO, F28 FY88, IRELAND

Notified body for EU Type Examination

SATRA TECHNOLOGY EUROPE LTD, (NB. 2777)

Bracetown Business Park, Clonee, Dublin D15 YN2P, Ireland

PRODUCT CODE	EN388:2016 +A1:2018 LEVEL ACHIEVED					EN ISO 11393-4:2019 LEVEL ACHIEVED	Size	(NB) NO
	A	B	C	D	E			
A290	2	1	2	2	X	CLASS 0, TYPE A	9/L-10/XL	2777

EN USER INSTRUCTIONS

PRODUCT CODE *See table above*

Refer to the product label for detailed information on the corresponding standards. Only standards and icons that appear on both the product and the user information below are applicable. All these products comply with the requirements of Regulation (EU) 2016/425 and Regulation 2016/425 on Personal Protective Equipment, as amended to apply in GB.

CAREFULLY READ THESE INSTRUCTIONS BEFORE USING THIS PRODUCT

This product is designed to minimise the risk of injury from a chainsaw. The left hand glove contains protective material to reduce the risk of injury from a chainsaw. The right hand glove does not contain any protective material to protect from chainsaws. The chainsaw shall be used correctly using both hands according to the instructions from the chainsaw manufacturer. Always remember that no item of PPE can provide full protection and care must always be taken whilst carrying out a risk related activity.

NOTE:

For properties A-E (EN388) the test sample is taken from the palm area of the glove. The gloves/sleeves should not come in contact with a naked flame. They will not prevent crushing injuries and associated vibrations. Products which achieve a level 1 or higher in tear resistance are not recommended for use where there is a risk of entanglement near moving machinery. Impact Protection applies to the back of the hand only and does not include the fingers. Where the performance is indicated with an X, instead of a number, means the glove is not designed for the use covered by the corresponding test. For property F Impact Resistance, if P is not indicated these gloves have not been tested for Impact. A blank box indicates this product has not been tested to the corresponding test.

For dulling during the cut resistance test (6.2), the coupe test results are only indicative while the TDM cut resistance test (6.3) is the reference performance result.

FITTING AND SIZING *See table above*

Only wear products of a suitable size. Products which are either too loose or too tight will restrict movement and will not provide the optimum level of protection. The size of these products is marked on the glove. See table above for size range. Sizing Conforms to EN ISO 21420 : 2020

DONNING & DOFFING:

These gloves are provided in a pair with a left hand and a right hand. The rubberised impact protection should be worn on the back of the hand, the printed label should be clearly visible on the back of the hand. Where there are impact protection pads, these should be worn on the back of the hand. For removal, avoid contact with any possible contaminants that may be on the gloves. Avoid reversing them inside out

STORAGE AND TRANSPORT

When not in use, store the product in a well ventilated area away from extremes of temperature. If the product is wet, allow it to dry fully before placing into storage.

INSPECTION BEFORE AND AFTER USE:

Always check the gloves before use. If the product becomes damaged it will NOT provide the optimum level of protection and must be discarded and replaced. Never use a damaged product. If in doubt consult the manufacturer.

CLEANING:

The performance levels are for products in a new condition and cannot be guaranteed if the product is laundered.



Hence it is recommended that these products should not be washed or dry cleaned.

MARKING- THE PRODUCT IS MARKED WITH:

- The CE Mark / ANSI Mark / UKCA/
- The Manufacturer/Authorised representative
- The product code
- The size
- The pictogram with the relevant standard number and performance figures.

PERFORMANCE AND LIMITATIONS OF USE-

Some gloves might contain ingredients (eg Latex) which are known to be a possible cause of allergies in sensitised persons, who may develop irritant and/or allergic contact reaction. If allergic reactions should occur, obtain medical advice immediately.

A list of substances contained within the gloves which are known to cause an allergies, shall be supplied on request. To avoid the risk of deterioration, it is advised that this product is used within 3 years of the final purchase date.

SEE RESULTS TABLE ABOVE

EN388:2016+A1:2018

LEVEL RANGE

A Abrasion Resistance	0-4
B Blade Cut Resistance	0-5
C Tear Resistance	0-4
D Puncture Resistance	0-4
E Straight Blade Cut Resistance	A-F
F Impact Resistance	P

EN388:2016
+A1:2018



EN ISO
11393-4:
2019



EN ISO 11393-4:2019	
Design Type	A-B
Class Performance level	0 -16m/s
	1 -20m/s
	2 -24m/s
	3 -28m/s

WARNING: THIS PRODUCT IS NOT A SUBSTITUTE FOR THE SAFE OPERATION OF A CHAINSAW AND DOES NOT PROVIDE FULL PROTECTION

0 : Indicates that the glove falls below the minimum performance level for the given individual hazard