

FT20 - Lite Trainer OB SR

Collection: Portwest Occupational

Range: Foot Protection

Material Upper: Flyknit Polyester

Material Outsole: EVA/Rubber

Inner Pack: 1

Outer Carton: 6

Product information

This lightweight occupational trainer is 100% metal free, and has an upper in stretchy textile aiding a more snug fit. It has a dual density phylon rubber outsole for superior grip and energy absorption.

Portwest Occupational Foot Protection

Innovation, design, styling and quality components define the Portwest foot protection collection.

Standards

EN ISO 20347:2022 OB (SR)



Features

- Slip resistant outsole
- 100% metal free
- Anti-static footwear
- Energy absorbing seat region
- Dual density sole unit
- Superbly cushioned comfort foot bed reducing foot fatigue
- New style
- SR
- CE certified
- UKCA marked

FT20 - Lite Trainer OB SR
Commodity Code: 6404199000

Test House

CTC (Notified Body No.: 0075)
 4, rue Hermann Frenkel
 Cedex 07, France
 Cert No: 0075/2085/161/12/23/2083

Carton Dimensions/Weight

Item	Colour	Len	Wid	Hgt	Weight(Kg)	Cubic(m ³)	EAN13	GTIN/DUN14
FT20BKR36	Black	50.0	40.0	34.0	0.6270	0.0680	5036108401932	15036108886767
FT20BKR37	Black	50.0	40.0	34.0	0.6600	0.0680	5036108401949	15036108886774
FT20BKR38	Black	50.0	40.0	34.0	0.6940	0.0680	5036108401956	15036108886781
FT20BKR39	Black	50.0	40.0	34.0	0.7080	0.0680	5036108401963	15036108886798
FT20BKR40	Black	50.0	40.0	34.0	0.7380	0.0680	5036108401970	15036108886804
FT20BKR41	Black	50.0	40.0	34.0	0.7590	0.0680	5036108401987	15036108886811
FT20BKR42	Black	50.0	40.0	34.0	0.7680	0.0680	5036108401994	15036108886828
FT20BKR43	Black	42.0	40.0	36.0	0.8250	0.0605	5036108402007	15036108886835
FT20BKR44	Black	42.0	40.0	36.0	0.8590	0.0605	5036108402014	15036108886842
FT20BKR45	Black	42.0	40.0	36.0	0.8780	0.0605	5036108402021	15036108886859
FT20BKR46	Black	42.0	40.0	36.0	0.9000	0.0605	5036108402038	15036108886866
FT20BKR47	Black	42.0	40.0	36.0	0.9090	0.0605	5036108402045	15036108886873
FT20BKR48	Black	42.0	40.0	36.0	0.9340	0.0605	5036108402052	15036108886880